

PP8G

Universal Glossy Polypropylene Banner



Outré ink jet materials are manufactured to meet or beat original equipment manufacturer's specifications. PP8G is a universal glossy polypropylene banner for indoor use. PP8G is compatible with a wide variety of wide format thermal and piezo inkjet printers using pigment and dye inks. This economical banner may be used for trade show graphics, retail POP, and promotional signage.

Physical Properties	
	PP8G
Basis Weight	154 g
Caliper	8 mil
% Opacity	98%
Whiteness	128
Adhesive Type	Permanent
Indoor Life Expectancy	6 mos. (UV inks)

Application Guidelines

Application Use: This product is recommended for indoor banner applications. This product is not water-resistant.

Printer & Ink Compatibility: PP8G can be printed with Hewlett-Packard DesignJet®, Epson Stylus , Color-Span® Displaymakers, and other piezo water-based systems equipped with pigment inks. It is recommended to use pigment inks for longer-lasting images. Although dye-based inks provide a higher color gamut, ink fade can occur. Inks NOT recommended for use are Ilford® Archiva™ inks because of premature fading is known to occur.

Product	HP DesignJet		Epson Stylus		ColorSpan Displaymaker		Roland/Mimaki/Mutoh		Canon	
	Dye	Pigment	Dye	Pigment	Dye	Pigment	Dye	Pigment	Dye	Pigment
PP8G	•	•	•	•	•	•	•	•	•	•

Surface Protection: Let image dry 2 hours prior to laminating. Dirt and stains cannot be cleaned from the imaged surface and excessive folding or creasing can damage the imaged surface. Laminating is recommended to protect the surface from dirt, abrasion, and frequent handling.

Printing: Ink coverage of up to 250% is recommended. To optimize print quality, printers should be set for highest print quality, select the "HEAVY COATED PAPER" paper mode for pigment inks, and "PHOTO IMAGE GLOSS" for dye inks in the HP5500 series printers.

Color Calibration: ICC color profiles can be obtained for selected RIP, ink and printer combinations on the www.myoutre.com web page.

Material Handling & Storage: Once print is completed, roll imaged media onto a core until ready for posting. Folding of the material is not recommended. After use, the roll should be stored at 72° F (+/-5°) and in its original packaging in the poly bag for no more than 1 year.

Finishing Recommendations

Banner Installation: Improper installation can cause premature banner failure. It is recommended that a professional installer be used.

Tape & Stitched Hem: Standard high-tack banner tape can be used and is preferred to sewing, as the sewing process can scratch or cause coating pick-off. Follow the guidelines of the tape manufacturer. If sewing, it is recommended that the un laminated banners be stitched hem side up so that the sewing machine foot comes in contact with only the backside of the banner. For maximum reinforcement, a double-stitched hem with a double lock stitch, with a maximum of five stitches per inch and corner reinforcements are recommended.

Grommeting: Grommets should be placed in the hemline along the length of the banner so that the grommet is through two layers. Corner grommets should be placed where the length and width hems cross, so that the grommet is through four layers. A reinforced corner is also recommended to increase durability.

Laminating: Let image dry 12 to 24 hours before laminating. Cold pressure-sensitive adhesives typically provide the most aggressive bonds and are recommended.



www.myoutre.com

#1 Network
309 Professional Park Avenue
Effingham, IL 62401
Phone: 217-536-5737
Fax: 217-536-5141